Laserliner®

VideoFlex G2

FibreCamera G2 Micro 1,5 m

ø 6 mm

1,5 m
Focus 5 cm

Professional video inspection system for visually inspecting areas that are difficult to access

Rev 0213



Camera head (ø 6 mm) with LED-Lighting



3,0" LCD

- **The camera head at a FlexCamera** transfers pictures directly to a LCD-Monitor.
- **Problem locating:** the camera indicates what is behind or in objects, walls circuits or cables etc. even under worst light conditions, due to the LED-lighting.
- **REC-Function:** still picure and video can be **recorded** for a later analysis.
- **Waterproof camera head and cable.**
- **Ideal for difficult accessibly areas** due to the very small measuring head (ø 6 mm)
- **Multilingual On-Screen-Display**
- **Camera unit can be replaced** to suit application
- **Rotation:** The manual image rotation function enables the image to be rotated by 180° on the monitor.
- **Formattable SDHC-Card**
- **Webcam function**

TECHNICAL DATA
CAMERA HEAD ø 6 mm, waterproof, IP 68
CAMERA FOCUS 5 cm
SCREEN TYPE 3,0" LCD
RESOLUTION DISPLAY 320 x 240 pixel
RESOLUTION PICTURE / VIDEO 1280 x 960 pixel / 320 x 240 pixel
FORMAT PICTURE / FORMAT VIDEO JPEG / AVI
LED 3 luminosity degrees
ZOOM 4 x digital zoom in 10% steps
MEMORY 32 MB / Supports up to max. 8 GB SDHC card
LENGTH OF FLEX CABLE 1,5 m
INTERFACE USB 1.1
AUTO SHUT OFF 5 min
POWER SUPPLY 4 x AA 1,5 Volt batteries
WEIGHT incl. batteries and flexcamera 0,65 kg

VideoFlex G2
inclusive carrying case
+ FibreCamera G2 Micro 1,5 m
+ software for webcam function
+ batteries

Packing dimension (W x H x D)
450 x 375 x 125 mm

ARTICLE	ARTICLE NO.	EAN CODE	PU
VideoFlex G2 – 1,5 m	082.112A	4 021563 683598	2

DISPLAY 320 x 240 pixel · 3" LCD · 180° · ZOOM 4x

CAMERA 320 x 240 pixel · LED LIGHT · IP 68

REC · SD HC · USB · 4x AA · HARD

UMAREX GmbH & Co. KG · Donnerfeld 2 · 59757 Arnsberg · Germany · Tel. +49 2932 638-300 · Fax +49 2932 638-333 · laserliner@umarex.de · www.laserliner.com