

Laserliner®

VideoFlex G2

FlexCamera G2 1,5 m



1,5 m
Focus 5 cm

Professional video inspection system
for visually inspecting areas that are
difficult to access



Camera head (ø 9 mm)
with LED-Lighting

3,0" LCD

- The camera head at a FlexCamera transfers pictures directly to a LCD-Monitor.
- **Problem locating:** the camera indicates what is behind or in objects, walls circuits or cables etc. even under worst light conditions, due to the LED-lighting.
- **REC-Function:** still picture and video can be recorded for a later analysis.
- **Waterproof camera head and cable.**
- **Ideal for difficult accessibility areas** due to the very small measuring head (ø 9 mm)
- **Multilingual On-Screen-Display**
- **Camera unit can be replaced** to suit application
- **Rotation:** The manual image rotation function enables the image to be rotated by 180° on the monitor.
- **Formattable SDHC-Card**
- **Webcam function**

TECHNICAL DATA

CAMERA HEAD
ø 9 mm, waterproof, IP 68
CAMERA FOCUS 5 cm
SCREEN TYPE 3,0" LCD
RESOLUTION DISPLAY 320 x 240 pixel
RESOLUTION PICTURE / VIDEO 1280 x 960 pixel / 320 x 240 pixel
FORMAT PICTURE / FORMAT VIDEO JPEG / AVI
LED 3 luminosity degrees
ZOOM 4 x digital zoom in 10% steps
MEMORY 32 MB / Supports up to max. 8 GB SDHC card
LENGTH OF FLEX CABLE 1,5 m
INTERFACE USB 1.1
AUTO SHUT OFF 5 min
POWER SUPPLY 4 x AA 1,5 Volt batteries
WEIGHT incl. batteries and flexcamera 0,65 kg



VideoFlex G2

inclusive carrying case
+ FlexCamera G2 1,5 m
+ software for webcam function
+ batteries

Packing dimension (W x H x D)
450 x 375 x 125 mm

1,5 m
Focus 5 cm

ARTICLE	ARTICLE NO.	EAN CODE	PU
VideoFlex G2 – 1,5 m	082.112A	4 021563 683598	2

DISPLAY

320 x 240
pixel

3"
LCD

180°
rotation

ZOOM
4x

CAMERA

320 x 240
pixel

LED
LIGHT

IP 68

REC

SD

USB

4x
AA

HARD