

Laserliner®

VideoFlex G2

SnakeCamera G2 10 m



10 m
Focus 5 cm

Professional video inspection system
for visually inspecting areas that are
difficult to access – also
over great distances



Camera head (ø 9 mm)
with LED-Lighting

3,0" LCD

- The camera head at a FlexCamera transfers pictures directly to a LCD-Monitor.
- **Problem locating:** the camera indicates what is behind or in objects, walls circuits or cables etc. even under worst light conditions, due to the LED-lighting.
- **REC-Function:** still picture and video can be recorded for a later analysis.
- **Waterproof camera head and cable.**
- **Ideal for difficult accessibly areas** due to the very small measuring head (ø 9 mm)
- **Multilingual On-Screen-Display**
- **Camera unit can be replaced** to suit application
- **Rotation:** The manual image rotation function enables the image to be rotated by 180° on the monitor.
- **Formattable SD-Card**
- **Webcam function**

TopGuide G2

- **Guide sleeve** for mounting on the camera head
- The specially ground sleeve allows for **optimal gliding on uneven surfaces**, for example dirty pipes.
- **Reduces jamming and contamination** of the camera head.
- Suitable for **9 mm camera head**

TECHNICAL DATA

CAMERA HEAD
ø 9 mm, waterproof, IP 68
CAMERA FOCUS 5 cm
SCREEN TYPE 3,0" LCD
RESOLUTION DISPLAY 320 x 240 pixel
RESOLUTION PICTURE / VIDEO 1280 x 960 pixel / 320 x 240 pixel
FORMAT PICTURE / FORMAT VIDEO JPEG / AVI
LED 3 luminosity degrees
ZOOM 4 x digital zoom in 10% steps
MEMORY 32 MB / Supports up to max. 8 GB SD card
LENGTH OF FLEX CABLE 10 m
INTERFACE USB 1.1
AUTO SHUT OFF 5 min
POWER SUPPLY 4 x AA 1,5 Volt batteries
WEIGHT incl. batteries and flexcamera 1,75 kg



VideoFlex G2

inclusive carrying case
+ SnakeCamera G2 10 m
+ TopGuide G2
+ software for webcam function
+ batteries

Packing dimension (W x H x D)
450 x 375 x 125 mm

ARTICLE	ARTICLE NO.	EAN CODE	PU
VideoFlex G2	082.110A	4 021563 682294	2

