

Laserliner

VideoScope XL



3,5 m
DOF 3...7 cm

Compact inspection camera for visual inspections of areas which are difficult to access – featuring record function

Rev18W49



Camera head (ø 9 mm) with LED-Lighting 3,5" TFT colour display

- **The camera head at a FlexCamera** transfers pictures directly to a LCD-Monitor.
- **Problem locating:** the camera indicates what is behind or in objects, walls circuits or cables etc. even under worst light conditions, due to the LED-lighting.
- **Waterproof camera head and cable**
- **Ideal for difficult accessibly areas** due to the small measuring head (ø 9 mm)
- **Diversified application** with 3,5 m camera.
- Powerful object lighting thanks to **4 high-performance LEDs**
- **Extraneous light reduction:** contrasty LC-Display which provides an optimum display even under light irradiation.
- **Rotation:** The manual image rotation function enables the image to be mirrored and rotated by 180° on the monitor.

TECHNICAL DATA

CAMERA HEAD
ø 9 mm, water-resistant, IP 68
CAMERA FOCUS F3 cm - F7 cm
SCREEN TYPE 3,5" TFT colour display
CAMERA RESOLUTION 640 x 480 pixels
DISPLAY RESOLUTION 320 x 240 pixels
LED 5 brightness levels
ZOOM
2x digital zoom in 20% increments
LENGTH OF FLEX CABLE 3,5 m
POWER SUPPLY
4 x AA 1.5 V batteries
OPERATING TEMPERATURE
0 °C ... 45 °C
STORAGE TEMPERATURE
-10 °C ... 60 °C
WEIGHT (incl. batteries) 745 g



3,5 m
DOF 3...7 cm

VideoScope Plus
+ batteries

Packing dimension (W x H x D)
175 x 265 x 190 mm

ARTICLE	ARTICLE NO.	EAN CODE	PU
VideoScope XL	082.114A	4 021563 703111	2

CAMERA	640 x 480 pixel	LED LIGHT	IP 68	DISPLAY	320 x 240 pixel	3,5" LCD	180°	ZOOM 2x	4x AA
---------------	-----------------	-----------	-------	----------------	-----------------	----------	------	---------	-------